1			2	3		4		5		6		7	Pb RoH	S	8
				<u>B0±0.10</u> ▲						■ 050+05 = 010±0.10 = 0.25 = 0.25	5.00±0.30	P.C.B TOF	LAYOUT	nces are banned	
			$ \begin{array}{c} \text{MATIC} \\  \hline 0 & 1 \\  \hline 0 & 3 \\  \hline 0 & 4 \\  \hline 0 & 5 \\  \hline 0 & 2 \\ \end{array} $							■ 1007 ■ 100				/5-(1.5X0.6)	5.00
		1.Rating 2.Contac	CIFICATION ∶DC 30V 0.5A t resistance: ≤	0.03Ω;	Ĺ				0.20	<u>_</u> ( <u>4</u> )					
		4.Withsto 5.Insertio 6.life tes	on resistance: nd voltage: 500 on and extraction st: 5,000 cycles are impor	DVAC ; on force: 3 s.	—30N;				6 5 4 3 2 1 ND.	FLAT PIECE         SPRING PIECE         SPRING PIECE         SPRING PIECE         CONTACT FOOT	1 1 1 1 1 1 1 0TY	PBT BRASS SUS301 BRONZE BRONZE BRONZE MATERIAL			Ag-Plating Ag-Plating Ag-Plating Ag-Plating Ag-Plating <b>REMARK</b>
						DEGICH	Starra	10/ (00 // 7		GENERAL TOLERANCE LESS OTHERWISE SPECIFIED General Angle		SHE			限公司
	- 0 '	12'/06/13	NEW	Steven	Max.hu	DESIGN CHECK	Jason	12'/06/13		X ± 0.50 X ° X.X ± 0.30 X.X ° X.X ± 0.20 X.X ° X.XX ± 0.10	± 3º ± 2º	CUSTORMER Copy Part ND.	<b>TITLE:</b>	PHO PJ-D30	<b>dne jack</b> 58H
ECN(DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	APPRO.	Max.hu	12'/06/13		PROJ: $\oplus$	SCALE: 3:	UNIT:mm	REV:		SHEET: 1 OF